

# ZXHN F600W Datasheet

ZXHN F600W is a GPON Optical Network Terminal designed for FTTH scenario. It provides video (IPTV), high speed internet access and Wi-Fi for home network connection. It has a small, smart appearance and green, energy-saving advantage.

## GPON Interface

- Optical port : 1 x GPON interface (SC/APC)
- Transmission Distance: 0 ~ 20km
- Transmit rate: 2.488Gbps downstream; 1.244Gbps upstream

## User Network Interface


- 4 x 10/100/1000Base-T; Half/full duplex; Auto MDI/MDIX; Auto negotiation
- 1 x Wi-Fi interface: IEEE 802.11b/g/n @2.4G Hz
- 1 x USB host interface

## Optical Module

- Wavelength:  
Receiving: 1480~1500 nm  
Transmitting: 1290~1330 nm
- Receiving Sensitivity: -28dBm
- Transmitting Optical Power: 0.5~5dBm

## Physical Performance

- Power consumption: <8W
- Dimensions: 220mm(W) x 44mm(H) x 160mm(D)
- Working temperature: 0°C ~ 40°C
- Working humidity: 5% ~ 95%
- Weight: about 300g
- Power supply: 12 V DC
- Mounting mode: Desktop/Wall mounting
- Supports hidden and coiled fiber



## Main Function

- Supported service: Internet, IPTV
- GPON: 8 T-CONTs, 32 GEM Ports
- VLAN: 802.1Q, 802.1P, 802.1ad
- MAC address table: 1k
- L3 function: DHCP server/Client, DNS Client/Relay, NAT
- IPv6: Dual Stack, DS-Lite
- Wi-Fi: 4 SSIDs, 2x2 MIMO, WPS
- Wi-Fi authentication: Shared key, 128-bit WEP, WPA-PSK, WPA2-PSK, WPA-PSK + WPA2-PSK
- Multicast: IGMP v1/v2 Snooping/Proxy, MLD v1 Snooping
- Multicast group per user port: 256
- QoS: service flow classification based on physical port, MAC address, VLAN ID, VLAN priority level, IP address; SP/WRR/SP+WRR
- Management: local web management, OMCI, TR069
- USB: DLNA DMS, USB backup, 3G dongle