

# ZXHN F625 Datasheet

ZXHN F625 is a GPON Optical Network Terminal designed for FTTH scenario. It provides subscribers rich, colorful, individualized, convenient and comfortable triple-play services including voice, video (IPTV/CATV) and high speed internet access. It has a small, smart appearance and green, energy-saving advantage.

## GPON Interface

- Optical port : 1 x GPON interface (SC/APC)
- Transmission Distance: 0 ~ 20km
- Transmit rate: 2.488Gbps downstream; 1.244Gbps upstream

## User Network Interface

- 4 x 10/100/1000Base-T; Half/full duplex; Auto MDI/MDIX; Auto negotiation
- 2 x POTS interfaces
- 1 x RF coaxial connector for CATV

## Optical Module

- Wavelength:
  - Receiving: 1480~1500 nm
  - Transmitting: 1290~1330 nm
  - Third party wavelength: 1550~1560 nm
- Receiving Sensitivity: -28dBm
- Transmitting Optical Power: 0.5~5dBm

## Physical Performance

- Power consumption: <9W
- Dimensions: 220mm(W) x 34mm(H) x 187mm(D)
- Working temperature: 0°C ~ 40°C
- Working humidity: 5% ~ 95%
- Weight: about 450g
- Power supply: 12 V DC
- Mounting mode: Desktop/Wall mounting



## Main Function

- Supported service: VoIP, Internet, IPTV, CATV
- GPON: 8 T-CONTs, 32 GEM Ports
- VLAN: 802.1Q, 802.1P, 802.1ad
- MAC address table: 1k
- VoIP: SIP/H.248, G.711/G.722/G.729, T.30/T.38
- Multicast: IGMP v1/v2 Snooping
- Multicast group per user port: 256
- QoS: service flow classification based on physical port, MAC address, VLAN ID, VLAN priority level, IP address; SP/WRR/SP+WRR
- Management: local web management, OMCI, TR069